
COMPACT 2.0 mm Lumaflex Elite

Compact 2.0 mm with Lumaflex Elite is a gym floor incorporating a double tongue-and-groove layer of 18 mm plywood planks that provide stability and a uniform structure for resilient dance surfaces. They are made exclusively from birch, in conjunction with our Elite Continuous Cushion.



Warranty Protection

10 year product coverage and 15 year wear layer coverage. Refer to sample warranty document for complete coverage details.

Environmental Facts and LEED

For environmental facts and LEED credits, visit: tarkettsportsindoor.com/en/specs-and-data/environmental-fact-sheets and tarkettsportsindoor. com/en/specs-and-data/leed-information.

Maintenance Instructions

For maintenance instructions, please refer to the Omnisports maintenance guide at the following link: tarkettsportsindoor.com/en/specs-and-data/ care-and-maintenance.

Foam Underlayment Options

Omnisports Compact Lumaflex Elite uses Tarkett Sports' Elite Continuous Cushion that are ½" x 3" strips of foam, that act as a sleeper system. The system will achieve Class 5 regardless of the synthetic floor decided to use.

Sports Characteristics

Property	Standard	Value
Surface Finish Effect	ASTM F2772-11	Passed
Force Reduction	ASTM F2772-11	Class 5
Vertical Deformation	ASTM F2772-11	Passed
Ball Rebound	ASTM F2772-11	Passed

Surface Layer Technical Characteristics

Property	Standard	Value
Reaction to Fire	ASTM E648	Class 1 (Radiant Panel)
Static Load Tolerance	ASTM F970 (modified)	200 psi
Wear Layer	EN 429	0.80 mm
Taber Abrasion	ASTM D3389	0.02 g (1,000 Cycles)
Stain Resistance	ASTM F925	Excellent
Roll Width	EN 426/EN 427	2 m (6.5′)
Roll Length	EN 426/EN 427	23 m (75.5′)
Thickness	EN 428/EN 429	2.0 mm (0.079″)
Weight	EN 430	3.1 kg/m² (0.64 lbs./sq. ft.)

Compatible substrates include: properly constructed and prepared concrete, wood, asphalt, and cementitious underlayments. Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information. Tarkett Sports reserves the right to modify these specifications without affecting their compliance with standards. Some results may vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.

888.364.6541 tarkettsportsindoor.com

Available Colors for Compact 2.0 mm with Lumaflex Elite



The colors presented here are representations only. An actual sample is recommended for exact color evaluation and matching. This pattern has a 3" wide plank. Other wood patterns have a width of 2 ^{1/4}".

