

DANCEFLOOR

Cushioned Vinyl

Dancefloor is cushioned vinyl floor for dance that can be used in studios and on stages. It incorporates a foam backing to reduce strain and a textured, non-coated surface layer to provide the grip that dancers prefer.



*except recycled content

Warranty Protection

- 10-year wear layer and product defect coverage. Refer to sample warranty document for complete coverage.

Environmental Facts and LEED

- For environmental facts and LEED credits, contact your regional Tarkett Sports representative.

Maintenance Instructions

- For a complete maintenance guide, contact your regional Tarkett Sports representative.

Installation Methods

- Full Adhesive:** installation using Tarkett's Multi-Poxy adhesive, HS Sports Spray, or Multi-Set acrylic adhesive over the entire area (moisture tolerance: 98% RH using Multi-Poxy, 90% RH using HS Sports Spray, 83% using Multi-Set per ASTM F2170)
- Tarkolay:** installation over moisture barrier using Multi-Poxy adhesive (no moisture testing required)

Performance Characteristics

Property	Standard	Value
Force Reduction	ASTM F2569	Class 1
Slip Resistance	AS 4586	P3

Technical Characteristics

Property	Standard	Value
Roll Length	EN 426/EN 427	15 m (49')
Roll Width	EN 426/EN 427	2 m (6.5')
Thickness	EN 428/EN 429	3.5 mm (0.138")
Wear Layer Thickness	EN 429	0.65 mm
Weight	EN 430	3.3kg/m ² (0.72 lbs./sq. ft.)
Surface Finish	—	Matte/satin
Reaction to Fire	ISO AS 9239-1	8.6 kW/m ²
Static Electrical Discharge	EN 1815	< 2 kV on concrete
Thermal Resistance	EN 10456	Approximately 0.04 m ² K/W
Chemical Resistance	ISO 26987 (EN 423)	High resistance
Dimensional Stability	ISO 23999 (EN 434)	≤ 0.10%
Abrasion Volume Loss	EN 660: Part 2	Group T: ≤ 2.0 mm ³
Residual Indentation	ISO 24343-1 (EN 433)	≤ 0.20 mm
Castor Chair Test	ISO 4918 (EN 425)	No damage
Curl Resistance to Heat	ISO 23999 (EN 434)	≤ 8 mm
Light Fastness	EN ISO 105-B02	≥ level 6

Compatible substrates include: properly constructed and prepared concrete, wood, asphalt, and cementitious underlayments. Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information. Tarkett Sports reserves the right to modify these specifications without affecting their compliance with standards. Some results may vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.


888.364.6541
tarkettsportsindoor.com




THE ULTIMATE
SURFACE EXPERIENCE



Available Colors for Dancefloor



Black



Grey

The colors presented here are representations only. An actual sample is recommended for exact color evaluation.