

DROPTILE

Droptile

Droptile is an elevated rubber tile system that is designed for comfort, impact noise reduction, and durability. It is ideal for areas where free weights and heavy exercise equipment are common.



Warranty Protection

- 15-year comprehensive product coverage. Refer to sample warranty document for complete coverage details.

Environmental Facts

- For environmental facts, visit: tarkettsportsindoor.com/en/specs-and-data/environmental-fact-sheets.

Maintenance Instructions

- For a complete maintenance guide, visit: tarkettsportsindoor.com/en/specs-and-data/care-and-maintenance.

Installation Method

- Quad Blok Connector System: Each Droptile is connected using a quad blok connector system, fastening each tile together. Since Droptile has a 1" thickness, reducers are used on the edges of the installation to transition to lower profile areas. Glue is used to provide adhesion from the blok to the tile.

Technical Characteristics

Property	Standard	Value
Reaction to Fire	ASTM E648	Passed (Radiant Panel)
Slip Resistance	ASTM D2047	> 0.9
Tensile Strength	ASTM D412	200 psi
Impact Insulation	ASTM E492-04	49
Sound Transmission	ASTM E413	51
Noise Reduction	ASTM C423	0.10 Sabine Per Square Foot
Taber Abrasion	ASTM D3389	Maximum 0.1 mg per cycle
Static Load	ASTM F970 (modified)	400 psi
Elongation	ASTM D412	40%
Flexibility	ASTM F137	Pass 1/4" Mandrel
Wear Surface Material	—	Rubber/EPDM Rubber
Base Layer Material	—	Natural, SBR Blend, and Recycled Rubber
Surface Texture	—	Slight (Slip Resistant)
Thickness	—	1"
Tile Dimensions	—	24" x 24"
Weight	—	19.5 kg/m ² (4 lbs./sq. ft.)
Profile Reducer Dimensions	—	48" x 4" x 1"

Compatible substrates include: properly constructed and prepared concrete, wood, asphalt, and cementitious underlayments. Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information. Tarkett Sports reserves the right to modify these specifications without affecting their compliance with standards. Some results may vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.

888.364.6541
tarkettsportsindoor.com




Available Colors for Droptile




Black DZ00


Group 2 - 20% Color




Fire Fly DZ47



Whey Protein 2
DZ97A



Deep Ocean DZ45




Smoke DZ46


Group 3 - 30% Color




Raiders DZ503




Purple DZ101




Gold Mix DZ102




Red DZ104




Orange DZ106



Green DZ107B




Sand DZ100B




Sky Blue DZ103

Group 4 - 95% Color



Steel DZ15A



Cobalt Blue DZ500



Dark Grey DZ502



Desert DZ43

The colors presented here are representations only. An actual sample is recommended for exact color evaluation and matching.