

DROPZONE

Elite 22.5 mm

Dropzone Elite 22.5 mm is a dual-density flooring system that is intended for heavy weights and rigorous training. It provides comfort and durability for the toughest workouts.



Warranty Protection

- 10-year comprehensive product coverage. Refer to sample warranty document for complete coverage details.

Environmental Facts

- For environmental facts, contact Tarkett Sports Technical Service at 770-712-8540.

Maintenance Instructions

- For a complete maintenance guide, contact Tarkett Sports Technical Service at 770-712-8540.

Installation Methods

- Full Adhesive:** full glue installation using Tarkett's solvent-free Multi-Poxy adhesive over the entire surface area (moisture tolerance: 98% RH per ASTM F2170)
- If conditions require a moisture barrier, Dropzone Elite can be installed with Tarkett Sports' Tarkolay. This system requires no moisture testing.

Sports Characteristics

Property	Standard	Value
Force Reduction	ASTM F2772-11	Class 3 (38%)


Technical Characteristics

Property	Standard	Value
Slip Resistance	ASTM D2047	> 0.8
Tensile Strength	ASTM D412	> 200 psi
Abrasion Resistance	ASTM D3389 / EN 649	< 1 g (1,000 cycles)
Flexibility	ASTM F137	Pass (1/4" mandrel)
Rolling Load Tolerance	EN1569	Pass
Thermal Conductivity	ASTM C518	1.3 BTU/(hr - ft - °F)
Impact	EN1517	0.0 mm
VOC Compliance	ASTM D5116	Passed (CA Section 01350)
Indentation	EN1516	0.1 mm
Surface Texture	—	Slight
Total Thickness	—	22.5 mm (0.886")
Surface Thickness	—	10.5 mm (0.413")
Cushion Thickness	—	12 mm (0.472")
Roll Length	—	25' to 100'
Roll Width	—	4' (± 0.75")
Weight	—	4.2 lbs. per sq. ft.

Compatible substrates include: properly constructed and prepared concrete, wood, asphalt, and cementitious underlayments. Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information. Tarkett Sports reserves the right to modify these specifications without affecting their compliance with standards. Some results may vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.




Available Colors for Dropzone Elite 22.5 mm




Black DZ00


Group 2 - 20% Color




Fire Fly DZ47A



Smoke DZ46




Deep Ocean DZ45




Whey Protein DZ97A


Group 3 - 30% Color



Sky Blue DZ103




Red DZ104




Raiders DZ503


Group 4 - 95% Color




Steel DZ15A




Warm Grey DZ507



Cobalt Blue DZ500




Desert DZ43A




Medium Grey DZ504




Charcoal DZ505



Maroon DZ510




Dark Taupe DZ506



Green DZ509



Navy DZ508



Red Appeal DZ511



Dark Gray DZ502

The colors presented here are representations only. An actual sample is recommended for exact color evaluation and matching.