


DROPZONE

Flex

Dropzone Flex is constructed of vulcanized rubber, that comes with a marble surface design, which is built tough, flexible and performance-ready. This floor is engineered to hold up under constant traffic, sports activities and heavy sporting equipment.



Technical Characteristics

Property	Standard	Value
Elongation	ASTM D412	250%
Tensile Strength	ASTM D412	493 psi
Shore Hardness (Shore A)	ASTM D2240	70±5 (Wear Layer)
Reaction to Fire	ASTM E648	Class 1 (Radiant Panel)
Smoke Density (Non-Flaming)	ASTM E662	Passed
Coefficient of Friction	ASTM D1894	0.99
Abrasion Resistance (H-18 Wheels, 500g, 1000 cycles)	ASTM D3389	0.37g
Chemical Resistance	ASTM F925	Compliant
Static Load Limit (tested at 250 psi)	ASTM F970	≤0.003 (250 psi/ 24 hours)
Tear Resistance	ASTM D624	Passed
Tear Abrasion	ASTM D501	Passed
Resistance to Heat	ASTM F1514	Compliant
Wear Surface Material	—	Virgin Rubber
Thickness	ASTM F386	9.5 mm (0.374")
Thickness of Wear Layer	ASTM F410	2.3mm
Weight	—	12.6 lbs per tile
Base Layer Material	—	Blended Rubber
Tile Formats Options	—	Square-Edge, Interlocking
Tile Dimensions (Straight Edge)	—	24" x 24"
Tile Dimensions (Interlocking Tile)	—	24" x 24" (23" x 23" net)

Warranty Protection

- 8-year comprehensive product coverage. Refer to sample warranty document for complete coverage details.

Environmental Facts

- For environmental facts, visit: tarkettsportsindoor.com/en/specs-and-data/environmental-fact-sheets.

Maintenance Instructions

- For a complete maintenance guide, visit: tarkettsportsindoor.com/en/specs-and-data/care-and-maintenance.

Installation Methods

- TNA 965 Acrylic Adhesive: full glue installation using Tarkett's 965 Acrylic Adhesive over the entire surface area (moisture tolerance: 85% RH per ASTM F2170)
- TNA 975 Two Part Urethane Adhesive: full glue installation using Tarkett's 975 Two Part Urethane Adhesive over the entire surface area (moisture tolerance: 90% RH per ASTM F2170)

Format Options

- Straight Edge Tile: 24" x 24"
- Interlocking Tile: 24" x 24" (23" x 23" net)

Compatible substrates include: properly constructed and prepared concrete, wood, asphalt, and cementitious underlayments. Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information. Tarkett Sports reserves the right to modify these specifications without affecting their compliance with standards. Some results may vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.

Color Options

Dropzone Flex comes with 8 color options, which makes it easy to create unique gym flooring or match the colors of a school or team.



Colors



Brown DZ283



Dark Maple DZ473



Blue DZ710



Grey DZ048




Beige DZ280



Marine Blue DZ030



Red DZ741



Black DZ790

The colors presented here are representations only. An actual sample is recommended for exact color evaluation and matching.