

# DROPZONE

Speckle

Dropzone Speckle is an 8 mm rubber surface with EPDM color chips that is intended for weight room and fitness areas. It is available in rolls, square-edge tiles, and interlocking tiles.



## Warranty Protection

- 3-year comprehensive product coverage. Refer to sample warranty document for complete coverage details.

## Environmental Facts

- For environmental facts, visit: [tarkettsportsindoor.com/en/specs-and-data/environmental-fact-sheets](http://tarkettsportsindoor.com/en/specs-and-data/environmental-fact-sheets).

## Maintenance Instructions

- For a complete maintenance guide, visit: [tarkettsportsindoor.com/en/specs-and-data/care-and-maintenance](http://tarkettsportsindoor.com/en/specs-and-data/care-and-maintenance).

## Installation Methods

- Full Adhesive:** full glue installation using Tarkett's solvent-free Multi-Poxy adhesive over the entire surface area (moisture tolerance: 98% RH per ASTM F2170)
- Dropzone Comfort can be installed using Tarkett Sports' Beybond 50 adhesive. With Dropzone Comfort, Beybond 50 can tolerate up to 92% RH per ASTM F2170.
- If conditions require a moisture barrier, Dropzone Speckle (rolls only) can be installed with Tarkett Sports' Tarkolay. This system requires no moisture testing.
- Interlocking Tile:** installation without adhesive using interlocking tiles

## Technical Characteristics

Property	Standard	Value
Slip Resistance	ASTM D2047	> 0.9
Tensile Strength	ASTM D412	200 psi
Impact Insulation	ASTM E492-04	54
Sound Transmission	ASTM E413-04	54
Noise Reduction	ASTM C423-08a	0.1
Static Load Tolerance	ASTM F970 (modified)	400 psi
Elongation	ASTM D412	75%
Flexibility	ASTM F137	Passed
CA Section 01350 Compliance	ASTM D5116	Passed
Chemical Resistance	ASTM F925	Excellent
Surface Texture	—	Slight
Thickness	—	8 mm (0.315")
Interlocking Tile Dimensions	—	23" x 23"
Square-Edge Tile Dimensions	—	36" x 36", 24" x 24"
Standard Roll Dimensions	—	4' x 30'
Weight	—	8.4 kg/m <sup>2</sup> (1.73 lbs./sq. ft.)

Compatible substrates include: properly constructed and prepared concrete, wood, asphalt, and cementitious underlayments. Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information. Tarkett Sports reserves the right to modify these specifications without affecting their compliance with standards. Some results may vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.




## Available Colors for Dropzone Speckle

### Group 1



Black DZ00


### Group 2 - 10% Color




Blue DZ01




Grey DZ02




Blue Grey DZ04




Fire Red DZ05




Ember DZ06



Yellow DZ07




Plum DZ09




Green Tea DZ32B


### Group 3 - 20% Color




Smoke DZ46



Fire Fly DZ47




Deep Ocean DZ45




Whey Protein DZ97A


### Group 4 - 30% Color




Sand DZ100B




Purple DZ101




Gold Mix DZ102




Sky Blue DZ103




Red DZ104



Orange DZ106




Raiders DZ503



Green DZ107B


### Group 5 - 95% Color



Desert DZ43A



Dark Grey DZ502



Steel DZ15A

The colors presented here are representations only. An actual sample is recommended for exact color evaluation and matching.