

# DROPZONE

Elite 22.5 mm

Dropzone Elite 22.5 mm is a dual-density flooring system that is intended for heavy weights and rigorous training. It provides comfort and durability for the toughest workouts.



## Warranty Protection

- 10-year comprehensive product coverage. Refer to sample warranty document for complete coverage details.

## Environmental Facts

- For environmental facts, contact Tarkett Sports Technical Service at 770-712-8540.

## Maintenance Instructions

- For a complete maintenance guide, contact Tarkett Sports Technical Service at 770-712-8540.

## Installation Methods

- Full Adhesive: full glue installation using Tarkett's solvent-free Multi-Poxy adhesive over the entire surface area (moisture tolerance: 92% RH per ASTM F2170)

## Sports Characteristics

Property	Standard	Value
Force Reduction	ASTM F2772-11	Class 3 (38%)

## Technical Characteristics

Property	Standard	Value
Slip Resistance	ASTM D2047	> 0.8
Tensile Strength	ASTM D412	> 200 psi
Abrasion Resistance	ASTM D3389 / EN 649	< 1 g (1,000 cycles)
Flexibility	ASTM F137	Pass (1/4" mandrel)
Rolling Load Tolerance	EN1569	Pass
Thermal Conductivity	ASTM C518	1.3 BTU/(hr - ft - °F)
Impact	EN1517	0.0 mm
VOC Compliance	ASTM D5116	Passed (CA Section 01350)
Indentation	EN1516	0.1 mm
Surface Texture	—	Slight
Total Thickness	—	22.5 mm (0.886")
Surface Thickness	—	10.5 mm (0.413")
Cushion Thickness	—	12 mm (0.472")
Roll Length	—	25' to 100'
Roll Width	—	4' (± 0.75")
Weight	—	4.2 lbs. per sq. ft.


Compatible substrates include: properly constructed and prepared concrete, wood, asphalt, and cementitious underlayments. Refer to current installation guidelines, ASTM F710, ACI 302.2R, and other industry standard recommendations for more information. Tarkett Sports reserves the right to modify these specifications without affecting their compliance with standards. Some results may vary in relation to certain flexibilities found within specified testing procedures and manufacturing tolerances.




## Available Colors for Dropzone Elite 22.5 mm

Black DZ00


### Group 1 - 0% Color




gZanDZ),6



HbdZDZ)+




9ZZeDZVc DZ)\*




LznEgdiZc DZ),6

### Group 2 - 0% Color




Sky Blue DZ103



Ged DZ10)


GVXgh DZ%'

### Group 4 - 95% Color




Steel DZ15A

BVgddc DZ%




LVgb<gZn DZ50,

9VgIVjeZ DZ%+




Cobalt Blue DZ500

<gZZcDZ%.



Desert DZ43A

CVknDZ%-



BZJb<gZn DZ%)

GZ%eeZVaDZ \*&

BA/ DZ% \*

9Vg<gVnDZ%'

The colors presented here are representations only. An actual sample is recommended for exact color evaluation and matching.